

## CNC Swiss Turning lathe HANWHA STL32/38 (-)

Ref: HANWHA STL32/38 (-)



## Tech specs

|                                        |                                           |
|----------------------------------------|-------------------------------------------|
| <b>Brand</b>                           | HANWHA                                    |
| <b>Model</b>                           | HANWHA STL32/38 (-)                       |
| <b>Number control</b>                  | Siemens 840D                              |
| <b>Max. machining diameter</b>         | Ø32/38                                    |
| <b>Z1 axis travel</b>                  | 320                                       |
| <b>Main spindle speed</b>              | 6,500                                     |
| <b>Spindle motor</b>                   | 23                                        |
| <b>No. of OD tools</b>                 | 5 (16mm)                                  |
| <b>Number of front tools</b>           | 4 (ER20M)                                 |
| <b>Nº of tools cross drill</b>         | 4 (ER20M)                                 |
| <b>Velocidad Taladrado transversal</b> | 6,000                                     |
| <b>Motor cross drill</b>               | 1,07                                      |
| <b>Nº of tools off-center drill</b>    | -                                         |
| <b>Sub spindle speed</b>               | 6,500                                     |
| <b>Sub spindle motor</b>               | 23                                        |
| <b>Nº tools of back tool</b>           | 3 (ER20M) (3 Fixed)                       |
| <b>Speed of back tool</b>              | -                                         |
| <b>Motor of back tool</b>              | -                                         |
| <b>External dimensions</b>             | 3,130 x 1,860 x 1,780                     |
| <b>Weight</b>                          | 4,400                                     |
| <b>Electrical power consumption</b>    | 40kVA, 26.7kW (VCTF 16SQ x 4C)            |
| <b>Air flow rate</b>                   | 20 ~ 30 (Hydraulic device capacity : 30L) |

**Central**

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

**Delegation IBI**

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

## Images

