

Pinnacle BX700A 5 Axes Machining Center

Ref: PINNACLE BX-700A



Tech specs

Brand	PINNACLE
X Axis stroke	1.400
Y Axis travel	710
Z Axis stroke	810
Spindle nose to table surface	180 - 990
T slot (WxDxN)	18x125x5
Working table area (LxW)	1.600x700
Table diameter (Ø)	630
Spindle Nose	DIN40
Spindle inner diameter	70
Spindle center to column	760
Spindle Speed	15.000
Draw bar force	900 ± 100
Main motor	15/ 19.4
Motor type	E+A mW16/17-8
Motor torque	71.6/ 172
Driver type	Worm gear
Reduction ratio	1:120
Tilting range	±120°
Driver type (Table)	Worm gear
Type	Separado
Diameter of table hole	75
Rotation speed	11.1
Min. indexing increment	0.001
Working torque	765
Clamp torque	1.765
Feed motor X/Y/Z	36/ 36/ 24
X/Y/Z Axis cutting feedrate	10000
Rated torque X/Y/Z	18.1/ 18.1/ 18.1
B Axis rated torque	11
C Axis rated torque	11
Auto tool changer ATC type	PLATO
Auto tool changer Cam type	DUAL ARM
Tool selection (Bi-Direction)	RANDOM
Tool storage capacity	30

Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Max. Tool Diameter	75
Max. Tool Length	250
Max. Tool Weight	8
Positioning XYZ linear axis	0.005
Positioning BC rotary	14"/ 14"
Repeatability XYZ linear axis	0.003
Repeteability BC rotatory	8"/ 8"
Air supply	6
Required voltage	380
Power requirement	40
Coolant tank capacity	450
Machine weight	11.000
Machine Height	3.200
Floor space (LxW)	3.890x3.180

Images

