

Lathe CNC Tongtai TMT2000-T3Y2

Ref: TMT2000-T3Y2



Tech specs

Brand	TONGTAI
Model	TMT2000-T3Y2
Spindle Bearing Diameter	100
Max. Swing Diameter	720
Max. swing over saddle	310
Max. turning diameter	320
Max. turning length	600
Spindle Nose	A2-6
Spindle Speed	4.500
Chuck size	8
Through-Spindle Hole diameter	76
Bar capacity	65
Min CS axis indexing increment	0.001
Spindle nose (Sub spindle)	A2-6
Chuck size (Sub spindle)	8
Through-Spindle Hole diameter	62
Spindle bearing diameter (Sub spindle)	100
Min (Sub spindle)	0.001
Tool capacity	12V: BMT-65/ 16V:BMT-55
Tool storage capacity	12x2
O.D. Tool	25x25
I.D. Tool	40
Max. Tool Diameter	20/ M16
Max speed	6.000
Spindle Motor	15/ 11
motor	5.5/3.7
X/Y/Z/B axis servo motor	4/ 3/ 4/ 3
sub-spindle motor	18.5/ 11
Coolant tank capacity	700
Coolant motor	0.55/ 1.1/ 0.55
Hydraulic tank capacity	40
Hydraulic motor	3HPx4P
Drive system	Servo
Spindle center to floor	1.300
Index time	0.3

X1/X2/X3 axis stroke	230/ 205/ 230
Y1/Y2/Y3 axis stroke	±51/ -/ ±51
Z1/Z2/Z3/B axis stroke	440/ 600/ 440/ 680
X/Y/Z/B axis rapid traverse	36/ 15/ 36/ 30
Bar capacity (Sub spindle)	51
Min. Cs axis indexing increment (Sub spindle)	0.001
Floor space (LxWxH)	4.100x2.600x2.500
Weight	10630

Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Images

