

Torno CNC Tongtai TNL-130H

Ref: TNL 130H



Tech specs

Brand	TONGTAI
Model	TNL-130H [HS/ HL/ HLS/ HLSB]
X Axis stroke	200
Z Axis stroke	400 [400/ 600/ 600/ 600]
Max. Swing Diameter	400
Max. swing over saddle	310
Max. turning diameter	320
Max. turning length	400
Spindle Speed	2.500
Spindle Nose	A2-8
Chuck size	10
Bar capacity	75
Through-Spindle Hole diameter	86
Spindle Bearing Diameter	130
Spindle center to floor	1.000
Min CS axis indexing increment	- [0.001/ - 0.001/ 0.001]
Chuck size (Sub spindle)	6
Through-Spindle Hole diameter	- [- / - / - / 35]
Min (Sub spindle)	- [- / - / - / 5(0.001)]
Tool storage capacity	12
O.D. Tool holder	25x25
I.D. Tool holder	40
Drive system	Hidráulico [Servo/ Hidráulico/ Servo/ Servo]
X/Z/B axis stroke	200/ 400 [400/ 600/ 600/ 600]/ - [- / - / - / 600]
X/Z Axis rapid traverse	20/24
Cutting feedrate	0.001 - 5.000 [0.001-5.000/ 0.001-5.000/ 0.001-5.000 / -]
Tailstock travel	400 [400/ 600/ 600/ -]
Spindle Inside taper	MT#5
Spindle motor	9/ 7.5
X/Z Axis servo motor	3.0/ 3.0
Coolant motor	0.37
Hydraulic motor	1.5
X Servo motor	3

Central

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

Delegation IBI

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

Z Servo motor	3.0
Z Axis rapid traverse	30
X Axis rapid traverse	24
Floor space (LxWxH)	2.350 [2.400/ 2.580/ 2.640/ 2.950]x1.860 [2.150/ 1.790/ 2.150/ 1.940]x2.010
Weight	4.300 [4.500/ 4.700/ 4.900/ 5.100]