

**Central**

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

**Delegation IBI**

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

## Takumi UB3222

Ref: TAKUMI UB3222



**Central**

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

**Delegation IBI**

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

## Tech specs

---

|                                               |                  |
|-----------------------------------------------|------------------|
| <b>Brand</b>                                  | TAKUMI & HURCO   |
| <b>Axes</b>                                   | 5                |
| <b>X Axis stroke</b>                          | 3200             |
| <b>Y Axis travel</b>                          | 2250             |
| <b>Z Axis stroke</b>                          | 1200             |
| <b>Spindle nose to table surface</b>          | 100 - 1300       |
| <b>Working table area (LxW)</b>               | 3320x2100        |
| <b>Max. Load (Workpiece Load)</b>             | 8500             |
| <b>T slot (WxDxN)</b>                         | 22x10x200        |
| <b>Spindle type</b>                           | Electromandrino  |
| <b>Spindle Speed</b>                          | 12.000           |
| <b>Main motor</b>                             | 25 / 30 (S6-40%) |
| <b>Spindle Nose</b>                           | HSK - A100       |
| <b>Lubrication method of the main spindle</b> | Aire - aceie     |
| <b>Cutting Feedrate</b>                       | 16/ 16/ 16       |
| <b>X/Y/Z Axis cutting feedrate</b>            | 10               |
| <b>C Axis rotation</b>                        | ±220             |
| <b>Positioning accuracy of the C axis</b>     | ±2               |
| <b>Max speed C axis</b>                       | 100              |
| <b>C Axis rated torque</b>                    | 810              |
| <b>B Axis stroke</b>                          | ±105             |
| <b>Positioning accuracy of the B axis</b>     | ±5               |
| <b>Velocidad máxima eje B</b>                 | 100              |
| <b>B Axis rated torque</b>                    | 382              |
| <b>Auto tool changer ATC type</b>             | Sombrilla        |
| <b>Tool storage capacity</b>                  | 32               |
| <b>Max. Tool Diameter</b>                     | 125              |
| <b>Max. Tool Length</b>                       | 300              |
| <b>Max. Tool Weight</b>                       | 15               |
| <b>Pneumatic pressure</b>                     | 6                |
| <b>Power requirement</b>                      | 70               |
| <b>Coolant tank capacity</b>                  | 1225             |
| <b>Machine weight</b>                         | 42.000           |
| <b>Floor space (LxW)</b>                      | 8.660x5.730      |
| <b>Machine Height</b>                         | 6.000            |

**Central**

Blanco Macael, s/n

Pol. Ind. Las Norias - 03670 Monforte del Cid (Alicante)

Telephone: +34 966 662 296 / FAX: +34 966 663 856

**Delegation IBI**

Avda. de la provincia, 73

03440 IBI (Alicante)

Telephone: +34 965 553 233 / FAX: +34 966 554 990

## Images

